

# **DENSO BUTYL PRIMER**

## **Butyl Tape Primer**

### **Description**

Denso Butyl Primer is a quick drying, solvent based, high-tack primer specifically designed to promote maximum adhesion.

### **Uses**

A fast drying butyl based primer for all surfaces prior to the application of various Denso Butyl tapes.

### **Features**

- Fills surface irregularities for intimate contact of tape compound
- Promotes high adhesion
- Fast drying
- Good penetration characteristics
- Can be brush or spray applied

### **Application**

Prepare surfaces by removing all loose scale, rust or other foreign matter by grit blasting or wire brush. Apply a thin uniform coat of Denso Butyl Primer to clean surface and allow to tack dry. Prime only areas to be wrapped the same day. Reprime if area becomes dirty or wet.



# Denso Butyl Primer

## PROPERTY SPECIFICATIONS

### PROPERTIES

% Solids	46% by wt.
Viscosity @ 73°F	200 cps
VOC	450 g/l
Minimum Application Temperature	25°F
Coverage	245 ft <sup>2</sup> /Gal
Color	Blue

### COVERAGE:

366 ft<sup>2</sup> per case - 1 quart containers

980 ft<sup>2</sup> per case - 1 gallon containers

### PACKAGING:

6 each 1 quart containers per case

4 each 1 gallon containers per case



**Unconventional Solutions, Inc. - Partnering with Your Industry to Repair - Protect - Upgrade**

MI HQ 28056 Oakland Oaks Ct., Wixom, MI 48393 | 248.735.7000 | [www.USIgroups.com](http://www.USIgroups.com)

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.