PRODUCT DATA SHEET

DENSO PASTE \$105

Wet/Underwater Petrolatum Tape Primer

Description

Denso Paste S105 is a soft petrolatum primer containing water displacing corrosion inhibiting and flow control additives. The primer can be applied by gloved hand or stiff bristle brush.

Uses

Denso Paste S105 serves as a corrosion inhibitor and aids in the application of petrolatum tapes. It is very effective underwater or on very wet metal surfaces such as pilings, risers, and H-piles.

Features

- Applied to marginally prepared surfaces (SSPC SP 2-3)
- · Applied to very wet or underwater surfaces
- · Contains no V.O.C.'s
- · Can be applied by inexperienced personnel
- · No shut downs necessary
- No cure time
- · Meets AWWA C-217
- · CSA Z245.30 compliant

Application

Prepare surfaces by removing all loose scale, rust or other foreign matter in accordance to SSPC SP2 "Hand Tool Cleaning" or SP3 "Power Tool Cleaning". High pressure water wash of 3,000 - 7,000 psi is also suitable. Apply a thin uniform coat of Denso Paste S105 to entire surface with gloved hand, brush or rag.



Denso Paste \$105

PROPERTY SPECIFICATIONS

PROPERTIES

 Solids Content
 100%

 Specific Gravity
 1.08

 Specific Volume
 26 cu in/lb.

 Flash Point
 >356°F

 Maximum Service Temperature
 158°F

 Coverage (Per Pail)
 10 to 22 ft²/lb.

 Packaging
 4 ea 5.5 lb tubs

COVERAGE PER CASE:

484 ft² per case for dry & wet surfaces

220 ft² per case for underwater applications

PACKAGING:

4 each 5.5 lb tubs per case

Also available in 55 lb pails



The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.